

Traglasten in t bei Auslegerlängen von 17 m bis 80 m - mit 12,0 t Winden:
50,5 t Ballast und 15 t Zentralballast

Radius (m)	Auslegerlänge in (m)												Radius (m)	
	17	20	26	32	38	44	50	56	62	68	74	80		
2,5	140.0	137.2												2,5
4	137.2	131.6	119.2											4
5	114.8	112.1	106.5	96.1	79.9									5
6	97.0	95.8	91.1	80.8	74.4	61.4	52.7							6
7	84.6	82.5	80.1	75.5	68.4	56.5	49.9	44.7	38.7	29.1				7
8	74.0	72.3	70.4	67.8	62.0	52.6	47.3	42.7	35.5	28.8	23.9	18.9		8
9	66.2	65.3	63.0	60.7	57.3	48.8	44.4	41.3	34.2	27.6	22.1	18.7		9
10	59.9	59.0	57.3	57.8	51.9	46.0	41.8	39.3	33.1	26.7	22.3	17.9		10
12	48.6	48.6	47.6	45.2	42.9	39.9	37.6	36.3	30.5	24.6	20.9	16.8		12
14	39.3	39.3	39.2	38.2	36.4	34.7	32.7	31.7	26.6	22.0	19.5	15.6		14
16	32.8	32.8	32.7	32.6	31.4	30.1	28.7	27.5	25.6	21.5	18.5	14.6		16
18		28.0	27.9	27.8	27.6	26.4	25.3	24.2	23.1	19.8	17.2	13.8		18
20		24.3	24.3	24.1	23.9	23.5	22.4	21.5	20.5	18.5	16.1	12.9		20
22			21.3	21.2	21.0	20.8	20.1	19.2	18.3	17.5	15.2	12.0		22
24			18.9	18.8	18.6	18.4	18.1	17.3	16.5	15.7	14.5	11.4		24
26			16.9	16.9	16.6	16.4	16.1	15.7	14.9	14.2	13.4	10.8		26
28				15.2	15.0	14.8	14.5	14.2	13.5	12.9	12.2	10.2		28
30				13.8	13.5	13.3	13.1	12.8	12.3	11.7	11.0	9.6		30
32				12.5	12.3	12.1	11.8	11.6	11.3	10.7	10.0	9.1		32
34					11.2	11.0	10.8	10.5	10.2	9.7	9.1	8.6		34
36					10.3	10.1	9.8	9.5	9.2	8.9	8.3	7.8		36
38					9.4	9.2	9.0	8.7	8.4	8.1	7.6	7.1		38
40						8.5	8.2	8.0	7.7	7.4	6.9	6.4		40
42						7.8	7.5	7.3	7.0	6.7	6.3	5.8		42
44							6.9	6.7	6.4	6.1	5.8	5.3		44
46							6.4	6.1	5.8	5.5	5.2	4.8		46
48							5.8	5.6	5.3	5.0	4.7	4.3		48
50								5.1	4.8	4.6	4.2	3.9		50
55									3.8	3.5	3.2	2.9		55
60										3.0	2.7	2.4	2.1	60
65											2.0	1.7	1.4	65
70												1.1		70

Oben angeführte Traglasttabellenwerte sind nur zur Information.
Für den aktuellen Hub verwenden Sie bitte die Traglastwerte aus dem Traglasttabellenbuch.